

Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)

Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

SCREEN TFT
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Precision

1.3. Details of the supplier of the safety data sheet

CRC Industries Europe bvba
Touwslagerstraat 1
9240 Zele
Belgium
Tel.: +32(0)52/45.60.11
Fax.: +32(0)52/45.00.34
E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Laurinkatu 57 A 23 B, 08100 Lohja	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Physical: Aerosol, category 3
Pressurised container: May burst if heated.



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

Classification is based on test data.

Health: Not classified

Classification based on calculation method.

Environment: Not classified

Classification based on calculation method.

Not flammable under normal conditions of use but contains flammable components

(Testing on flammability in closed space, FEA X610-E, are negative)

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Signal word: Warning

Hazard statement(s): H229 : Pressurised container: May burst if heated.

Precautionary statement(s): P102 : Keep out of reach of children.
P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 : Do not pierce or burn, even after use.
P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Supplemental Hazard information: 3 % by mass of the contents are flammable.
Contains:
1,2-benzisothiazol-3(2H)-one
May produce an allergic reaction.

Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons < 5 %
benzisothiazolinone, benzoic acid

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1.3-butadiene <	01-2119485926-20	68512-91-4	270-990-9	1-5	Press. Gas, Flam. Gas 1	H280,H220	K,G



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)

Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

0.1%)							
sodium salt of an alkyl ether sulfate2	01-2119488639-16	-	500-234-8 (NLP)	<0.1	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3	H315,H318,H412	X
Phosphoric acid, isononyl ester	01-2119982386-24	84988-61-4	284-851-5	<0.1	Skin Corr. 1C	H314	
Sulfonic acids, C14-17-sec-alkane, sodium salts	01-2119489924-20	97489-15-1	307-055-2	<0.1	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3	H302,H315,H318,H412	
Disodium metasilicate anhydrous	01-2119449811-37	6834-92-0	229-912-9	<0.1	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3	H290,H314,H335	
Amines, C12-14 (even numbered)- alkyl dimethyl, N-oxides	01-2119490061-47	-	(931-292-6)	<0.1	Eye Dam. 1, Acute Tox. 4, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2	H318,H302,H315,H400,H411	Q
1,2-benzisothiazol-3(2H)-one	-	2634-33-5	220-120-9	<0.05	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic Acute 1	H302,H315,H318,H317,H400	X

Explanation notes

G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einacs-nr. 203-450-8)

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

X : SCL (specific concentration limit)in accordance with art.10 of CLP Regulation No 1272/2008

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures**4.1. Description of first aid measures**

Contact with eyes :	If substance has got into eyes, immediately wash out with plenty of water
Contact with skin :	Wash with plenty of soap and water.
Inhalation :	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Ingestion :	If swallowed accidentally, do not induce vomiting and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	No adverse health effects expected
Ingestion :	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	May cause irritation.
Eye contact :	May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

General Advice : In case of accident or if you feel unwell, seek medical advice (show the label where possible)



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)

Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

If symptoms persist always call a doctor

SECTION 5: Firefighting measures

5.1. Extinguishing media

water, foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material
Wash spill site with water and detergent

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

Do not spray on a naked flame or incandescent material.
Do not pierce or burn aerosols, even after use.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Store in a well-ventilated place.
Store frost free
Keep out of reach of children.

7.3. Specific end use(s)

Cleaners - Precision

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

No information available

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
hands and skin :	For incidental contact with the product wear chemical-resistant gloves (standard EN 374). The use of disposable gloves is acceptable provided that they are changed immediately after a splash or spill. In all cases handle and use the product in accordance with good industrial hygiene practices.
Recommended gloves:	(neoprene)
eyes :	Wear safety eyewear according to EN 166.
Environmental protection:	Avoid release to the environment. Collect spillage.

SECTION 9: Physical and chemical properties



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)
Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Apperance : physical state : Propane/butane propelled liquid.
colour : Colorless.
odour : Odorless.
pH : 9 - 10
Boiling point/range : Not applicable.
Flash point : None
Evaporation rate : Not applicable.
Explosion limits : upper limit : Not applicable.
lower limit : Not applicable.
Vapour pressure : Not available.
Relative density : 1.0 g/cm³ (@ 20°C).
Solubility in water : Soluble in water
Auto-ignition : > 200 °C
Viscosity : Not applicable.

9.2. Other information

VOC = volatile organic compounds 35 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Avoid overheating
Store frost free

10.5. Incompatible materials

Strong oxidising agent



Productname : SCREEN TFT Creationdate : 29.06.17 Version : 4.0
 Ref.Nr.: BDS001400_3_20170629 (EN) Replaces: BDS001400_20130913

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met
skin corrosion/irritation: based on available data the classification criteria are not met
serious eye damage/irritation: based on available data the classification criteria are not met
respiratory or skin sensitisation: based on available data the classification criteria are not met
germ cell mutagenicity: based on available data the classification criteria are not met
carcinogenicity: based on available data the classification criteria are not met
toxicity for reproduction: based on available data the classification criteria are not met
STOT-single exposure: based on available data the classification criteria are not met
STOT repeated exposure: based on available data the classification criteria are not met
aspiration hazard: based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : No adverse health effects expected
Ingestion : Ingestion is unlikely to occur
Skin contact : May cause irritation.
Eye contact : May cause irritation.

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
Disodium metasilicate anhydrous	6834-92-0	LD50 oral rat	300-2000 mg/kg
		LC50 inhal.rat	1-5 mg/l
		LD50 derm.rat	>2000 mg/kg
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	-	LD50 oral rat	1064 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method
----------------------	---------	--------



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)

Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

Disodium metasilicate anhydrous	6834-92-0	IC50 algae	207 mg/l
		LC50 fish	210 mg/l
		EC50 daphnia	1700 mg/l
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	-	IC50 algae	0.143 mg/l
		LC50 fish	2.67 mg/l
		EC50 daphnia	3.1 mg/l

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No experimental data available

12.4. Mobility in soil

Soluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No experimental data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS



Productname : SCREEN TFT
Ref.Nr.: BDS001400_3_20170629 (EN)

Creationdate : 29.06.17 Version : 4.0
Replaces: BDS001400_20130913

14.3. Transport hazard class(es)

Class: 2.2
ADR/RID - Classification code: 5A

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (E)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.



Productname : SCREEN TFT	Creationdate : 29.06.17 Version : 4.0
Ref.Nr.: BDS001400_3_20170629 (EN)	Replaces: BDS001400_20130913

H290 : May be corrosive to metals.
H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

REVISIONS IN CHAPTRE : Labelling according to Regulation (EC) No 1272/2008
8.2. Exposure controls

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.